



## 1. General description

Promotes the sliding of unprocessed wood on working tables of wood processing machines. Colorless. Does not contain silicones.

## 2. Features

- Produces a very low coefficient of friction.
- Does not contain silicones.
- Suitable for all wood types.
- Safe on all metal surfaces, does not stain.

## 3. Applications

- Plastic drives and sliding mechanisms.
- Guide rails.
- Working and positioning tables of all wood working machines.

## 4. Directions

- Shake well before use.
- Use only with adequate ventilation.
- Test before use on sensitive materials.
- Do not use on energized equipment.
- Apply to a clean, dry surface.
- Spray from a distance of approximately 20 - 30 cm.
- Apply a thin even film.
- Repeat if necessary.
- Allow to dry completely before reactivation.
- **A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.**

## 5. Typical product data (without propellant)



Manufactured by :  
**CRC Industries Europe bvba**  
Touwslagerstraat 1  
9240 Zele Belgium  
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34  
**www.crcind.com**



